



VALVE PROGRESSIVE SIZE CHART

Indexed by Head Diameter



STEM TYPES



Head Diameter	Overall Length	Stem Diameter	Face Angle	Stem Type	Melling Part No.
.941	3.616	.2350	45	SG	V5390
0.890	3.265	.3128	45	D	V0285
0.906	3.390	.3100	45	SG	V0485
0.276	3.664	.1693	N/A	N/A	V5417
0.276	3.644	.1693	N/A	N/A	V5418
1.005	3.925	.2351	45	SG	V5177
1.015	4.077	.3128	44	SG	V0489
1.015	3.938	.3128	45	D	V0234
1.015	4.032	.3128	45	D	V0250
1.015	3.969	.3130	45	TG	V0824
1.031	4.180	.2350	45	SG	V5159
1.042	3.977	.2345	45	SG	V5180
1.062	3.954	.2355	45	SG	V5320
1.063	4.439	.2590	45	SG	V5188
1.071	3.787	.2350	45	SG	V5333
1.075"	3.740"	.236"	45	SG	V5306
1.075"	3.757"	.216"	45	SG	V5553
1.081	3.967	.2733	45	SG	V5521
1.082	3.860	.2350	45	SG	V5338
1.090	5.550	.2483	60	SG	V0759
1.094	3.390	.3100	45	SG	V0230
1.095	4.179	.2329	45	3G	V1921
1.102	3.800	.237	45	.237	V1746
1.102	4.102	.2347	45	SG	V5179
1.102	3.311	.2144	45	SG	V5170
1.102	4.508	.2579	45	SG	V5119
1.102 (27.99MM)	4.445 (112.90MM)	.2579 (6.55MM)	45	SG	V5081
1.103	3.988	.2350	45	SG	V5235
1.103 (28.02MM)	4.479 (113.77MM)	.2735 (6.95MM)	45	SG	V5080
1.106	3.866	.2731	45	SG	V5354
1.107	3.515	.2345	45	SG	V5258
1.130	4.614	.2328	45	SG	V1742
1.130	4.614	.2328	45	3G	V1992
1.138	3.919	.2348	45	SG	V5327

VALVE PROGRESSIVE SIZE CHART (Cont.)

Indexed by Head Diameter

Head Diameter	Overall Length	Stem Diameter	Face Angle	Stem Type	Melling Part No.
1.141	4.488	.2600	45	SG	V5187
1.141	3.934	.3137	45	SG	V5308
1.142	4.490	.2345	N/A	SG	V5535
1.142	4.496	0.2148	45	SG	V5542
1.142	4.862	.2147	45	SG	V5198
1.142	4.470	.2362	45	SG	V5259
1.142	4.260	.233	45	SG	V1941
1.150	4.529	.2160	45	SG	V5190
1.156	4.937	.3410	45	2G	V0312
1.160	3.977	.2349	45	SG	V5178
1.164	4.082	.2343	45	SG	V5285
1.172	5.355	.3870/.3863	45	SG	V1106+15
1.1720	5.355	.3720/.3713	45	SG	V1106
1.180	3.637	.2155	45	SG	V5224
1.180	3.814	.2347	45	SG	V5168
1.180	5.528	.3100	30	SG	V1500
1.181	4.311	.2744	45	SG	V1674
1.181	4.120	.2154	45	SG	V2007
1.181	4.745	.2591	45	SG	V5192
1.181	4.429	.2600	45	SG	V5186
1.181	3.982	.2580	45	SG	V5097
1.181	4.510	.2737	45	SG	V5102
1.181	4.027	.2342	45	SG	V5229
1.181	4.570	.2740	45	SG	V5256
1.181	3.594	.2350	45	SG	V5310
1.181 (30.00MM)	4.457 (113.21MM)	.2756 (7.00MM)	45	SG	V5113
1.181 (30.00MM)	4.409 (110.00MM)	.3116 (7.90MM)	45	3G	V5002
1.181 (30.00MM)	4.086 (103.78MM)	.3131 (7.95MM)	45	SG	V5033
1.183	3.600	.2355	45	SG	V5314
1.185	4.648	.2737	45	SG	V5252
1.185	3.931	.3130	45	SG	V5250
1.186 (30.12MM)	4.432 (112.57MM)	.2581 (6.56MM)	45	SG	V5057
1.198	4.316	.2575	45	SG	V5128
1.200	4.318	.233	45	SG	V1731
1.200	4.153	0.2576	45	SG	V5501
1.201	3.926	.2353	45	SG	V5176
1.203	3.953	.3145	30	TG	V0825
1.203	5.153	.3391	45	SG	V0837
1.203	4.016	.3145	30	D	V0251
1.203	5.173	.3381	45	D	V0170
1.203	4.352	.3384	44	SG	V0596
1.203	5.188	.3381	45	SG	V1147
1.218	3.936	.3125	45	SG	V5129
1.220	4.041	.3126	45	SG	V5099
1.220	4.140	.2740	45	SG	V5104
1.220	4.212	.2745	45	SG	V5106
1.220	4.173	.2350	45	SG	V5157
1.220	4.156	.273	45	SG	V5210
1.220	3.979	.2753	45	SG	V5183
1.220	4.718	.2740	45	SG	V5254
1.220	3.499	.2350	45	SG	V5257
1.220	3.632	.2350	45	SG	V5311
1.220	3.972	.2756	45	SG	V5262
1.220	4.041	.3126	45	SG	V5083
1.226	4.116	.3127	45	SG	V5369
1.226 (31.27 MM)	3.880 (98.5 MM)	.3127 (7.94 MM)	45	SG	V5006
1.227	3.875	.3127	45	3G	V5364
1.239	4.308	.2745	45	SG	V1727

VALVE PROGRESSIVE SIZE CHART (Cont.)

Indexed by Head Diameter

Head Diameter	Overall Length	Stem Diameter	Face Angle	Stem Type	Melling Part No.
1.239 (31.47MM)	4.265 (108.33MM)	.3097/.3087	45	3G	V1243
1.240	4.382	.3098	45	3G	V5089
1.250	4.016 (102.01MM)	.2585 (6.57 MM)	45	SG	V5098
1.250	4.437	.3095	45	SG	V1041
1.256	4.052	.2700	N/A	SG	V5115
1.258	3.859	.2350	45	SG	V5337
1.259	4.140	.2346	45	SG	V5181
1.259 (31.98MM)	4.409	.3123	45	3G	V5068
1.260	3.822	.237	45	SG	V1898
1.260	4.311	.2598	45	SG	V5185
1.260	4.043	.2745	45	SG	V5155
1.260	3.962	.2355	45	SG	V5318
1.260	4.559	.3150	45	SG	V5215
1.260	4.622	.3150	45	SG	V5280
1.260 (32.00MM)	3.896	.3127	44	SG	V1342
1.261	4.144	.2745	45	SG	V5118
1.264	3.759	.2745	45	SG	V5353
1.264	4.262	.3095	45	SG	V0564
1.271	3.996	.2738	45	SG	V5520
1.271 (32.99MM)	4.156 (105.56MM)	.3153 (8.00MM)	44	3G	V1300
1.272	3.798	.2345	45	SG	V1949
1.278	4.543	.273	45	SG	V5173
1.278	3.970	.3145	30	D	V0343
1.280	4.804	.3100	45	SPEC	V0173
1.280	4.562	.2747	45	SG	V5162
1.281	4.816	.3410	45	SG	V0220
1.281	4.700	.3410	45	TG	V0270
1.291	4.578	.2362	45	SG	V5260
1.296	4.613	.3500	45	3G	V5011
1.296 (32.92MM)	4.230 (107.44MM)	.3130 (7.95MM)	45	SG	V5079
1.297	4.778	.2750	45	SG	V5245
1.298	3.997	.2349	45	SG	V5234
1.298	5.341	.3520	45	SG	V5009
1.298	4.421	.235	N/A	SG	V5534
1.299	4.729	.3415	46	SG	V1558
1.300	4.437	.3137	45	SG	V5084
1.300	6.062	.3720	45	SG	V0592
1.300	4.680	.3427	44	SG	V1322
1.300 (33.02MM)	4.213 (107.01MM)	.3163 (8.03MM)	45	SG	V5060
1.301 (33.05MM)	4.735 (120.27MM)	.3414 (8.67MM)	45	SG	V1463
1.303 (33.10MM)	4.618 (117.30MM)	.3131 (7.95MM)	44	SG	V5014
1.306	3.569	.3130	45	3G	V5356
1.307 (33.20MM)	4.727 (120.07MM)	.3417/.341	45	2G	V1394
1.309	4.518	.2341		3G	V1991
1.309	4.512	.2340	N/A	SG	V1741
1.312	5.281	.3410	45	2G	V0503
1.313	5.156	.3725	45	2G	V0323
1.313	4.771	.308"	45	SG	V0249
1.316	4.502	.3110	45	SG	V0873
1.320	3.966	.2349	45	SG	V5325
1.328	4.957	.3411	30	2G	V0269
1.328	5.088	.3387	45	TG	V0361
1.328	5.198	.3386	44	SG	V0210
1.328	5.192	.3381	44	D	V0196
1.328	4.328	.3410	30	SG	V0597
1.331	4.260	.234	45	3G	V1920
1.331	4.618	.2356	45	3G	V2118
1.333 (33.86MM)	3.885 (98.68MM)	.3127 (7.94MM)	45	SG	V5007

VALVE PROGRESSIVE SIZE CHART (Cont.)

Indexed by Head Diameter

Head Diameter	Overall Length	Stem Diameter	Face Angle	Stem Type	Melling Part No.
1.335	4.851	.3140	45	SG	V5046
1.335	4.830	.3508	45	3G	V5349
1.336 (33.93MM)	4.303 (109.30MM)	.3130 (7.95MM)	45	SG	V5093
1.336 (33.93MM)	4.358 (110.69MM)	.3130 (7.95MM)	45	SG	V5086
1.337	4.316	.2588	45	SG	V5126
1.337	3.768	.3130	45	SG	V5140
1.338	3.990	.2351	45	SG	V5228
1.338	4.059	.2350	45	SG	V5284
1.338	4.606	.3150	45	SG	V5276
1.339	4.567	0.2161	45	SG	V5541
1.339	5.475	.2730	45	SG	V5523
1.339	4.125	.3132	45	3G	V5367
1.339	4.303	.3150	45	SG	V5317
1.339	5.208	.3130	45	SG	V5100
1.339	4.570	.2745	45	SG	V5163
1.339	4.570	.2745	45	SG	V5164
1.339	5.271	.3152	45	SG	V1545
1.339 (34.01MM)	4.441 (112.80MM)	.2593 (6.59MM)	45	SG	V5058
1.339 (34.01MM)	4.459 (113.26MM)	.2750 (6.98MM)	45	SG	V5082
1.340	4.624	.2740	45	3G	V1698
1.340"	3.748"	.236"	45	SG	V5305
1.340"	3.760"	.216"	45	SG	V5552
1.342	4.827	.3410	45	SG	V0162
1.342	4.937	.3410	45	2G	V0313
1.343	3.744	.3137	45	3G	V5368
1.344	4.777	.2745	45	SG	V5273
1.359	3.922	.3100	30	D	V0131
1.370	4.394	.234	45	SG	V1730
1.371	4.615	.3125	45	3G	V1535
1.375	5.355	.3410	45	SG	V0205
1.375	6.060	.3720	45	SG	V0921
1.375	4.643	.3407	45	SG	V0976
1.375	4.937	.3412	45	SG	V0989
1.375	5.524	.3386	44	SG	V1055
1.375	3.991	.3413	45	SG	V1337
1.375	4.586	.3400	45	SG	V1181
1.375	4.186	0.2588	45	SG	V5500
1.377	4.456	.2748	45	SG	V5112
1.377 (34.98MM)	4.409 (111.99MM)	.3126 (7.94MM)	45	SG	V5064
1.378	4.071	.2156	45	SG	V2006
1.378	4.278	.3126	45	SG	V5142
1.378	4.110	.2756	45	SG	V5265
1.378	3.929	.3137	45	SG	V5249
1.378	4.727	.3133	45	SG	V1465
1.378 (35.00MM)	4.508 (114.50MM)	.2598 (6.60MM)	45	SG	V5109
1.378 (35.00MM)	4.440 (112.78MM)	.2594 (6.59MM)	45	SG	V5078
1.379	4.198	.3135	44	SG	V1485
1.379	4.004	.2603/.2596	45	SG	V5136
1.379	4.748	.2735	45	SG	V5194
1.380	3.814	.2349	45	SG	V5167
1.380	5.541	.3103	30	SG	V1366
1.380	4.920	.3410/.3405	45	2G	V1371
1.380	5.120	.3422	45	2G	V1439
1.382	4.252	.2740	45	SG	V5271
1.383	4.806	.3415	45	4G	V1527
1.384 (35.20MM)	4.620 (115.35MM)	.3131 (7.95MM)	44	SG	V5036
1.388	4.262	.3094	44	SG	V1266
1.388	4.262	.3244	44	SG	V1266+15

VALVE PROGRESSIVE SIZE CHART (Cont.)

Indexed by Head Diameter

Head Diameter	Overall Length	Stem Diameter	Face Angle	Stem Type	Melling Part No.
1.394	4.443	.3112	45	4G	V1448
1.394	4.442	.3115	45	4G	V1540
1.394	4.521	.3116	45	4G	V1552
1.394	4.521	.3116	45	4G	V1554
1.395	4.984	.3715	45	2G	V0793
1.397	4.401	.3128	44	3G	V5005
1.397	3.784	.2355	45	SG	V5332
1.398	4.225	.232	45	SG	V1937
1.398	5.023	.272	45	4G	V1994
1.400	4.330	.2748	46	SG	V1673
1.400	6.411	.3104	30	SG	V0758
1.403	6.351	.3404	45	2G	V0690
1.406	5.047	.3725	45	2G	V0321
1.406	4.892	.3725/.3715	46	SG	V1045
1.406	4.892	.3720	44	4G	V1325
1.406	4.913	.3720	44	SG	V1297
1.415	4.140	.2742	45	SG	V5105
1.416	4.268	.3140	45	SG	V5323
1.417	3.972	.2756	45	SG	V5261
1.417	4.212	.2746	45	SG	V5107
1.417	4.550	.2737	45	SG	V5103
1.417	4.204	.3139	45	SG	V5161
1.417	4.313	.2599	44	SG	V5184
1.417	4.135	.3153	45	3G	V5386
1.417	4.319	.3131	40	SG	V5536
1.417 (35.99MM)	4.480 (113.79MM)	.3134 (7.96MM)	45	SG	V5037
1.417 (35.99MM)	4.155 (105.54MM)	.3164 (8.04MM)	45	SG	V5066
1.417 (35.99MM)	4.291 (108.99MM)	.3135 (7.95MM)	45	SG	V5071
1.418	4.315	.3134	45	SG	V5336
1.418 (36.02MM)	4.352 (110.54MM)	.3158/.3418	44	3G	V1199
1.419 (36.00MM)	4.476 (113.69MM)	.3137 (7.97MM)	44	SG	V5024
1.425	4.736	.3413	45	2G	V5225
1.425	4.737	.3417/.3410	45	2G	V1480
1.425	4.698	.3412/.3405	45	SG	V1363
1.437	4.076	.2750	46	SG	V5116
1.437	4.091	.2290	45	SG	V1703
1.438	4.932	.3425	45	SG	V1073
1.438	4.906	.3412	45	SG	V0155
1.440	4.857	.3725	45	SG	V0882
1.441	4.328	.2750	46	SG	V1726
1.448	4.942	.3414	45	SG	V1537
1.450	4.867	.3410	44	SG	V0742
1.450	4.873	.3415	44	SG	V1000
1.452	5.068	.3418/.3408	45	SG	V1135
1.452	5.068	.3568/.3558	45	SG	V1135+15
1.452	4.850	.275	N/A	3G	V1791
1.455	4.934	.3725	45	2G	V0912
1.456	5.165	.3136	45	SG	V1704
1.456	4.673	.2745	45	SG	V5251
1.456	4.443	.3140	45	SG	V5331
1.457	4.420	.3135	45	SG	V5330
1.457	5.141	.2735	45	SG	V1737
1.457	5.165	.3132	45	SG	V1568
1.457	4.980	.2738	45	SG	V1903
1.457	5.189	.3152	44	3G	V1451
1.457	4.708	.2746	45	SG	V5253
1.457	4.539	.2722	45	3G	V5560
1.460	4.593	.2745	45	SG	V5255

VALVE PROGRESSIVE SIZE CHART (Cont.)

Indexed by Head Diameter

Head Diameter	Overall Length	Stem Diameter	Face Angle	Stem Type	Melling Part No.
1.461	5.070	.3419/.3409	44	SG	V1327
1.462	5.010	.3418/.3411	44	SG	V1453
1.462	5.010	.3448/.3441	44	SG	V1453+3
1.463	4.840	.3414	45	4G	V1469
1.463 (37.16MM)	4.086 (103.78MM)	.3142 (7.98MM)	45	SG	V5031
1.467	4.583	0.2346	45	3G	V2119
1.470	4.974	.3116	45	4G	V1670
1.474	4.921	.3140	45	3G	V5343
1.475	5.047	.3129	45	SG	V5342
1.484	6.336	.4005	45	SG	V0679
1.484	3.926	.3100	30	D	V0132
1.487	4.727	.3405	45	SG	V1710
1.494	4.579	.3138	45	SG	V5085
1.495	5.335	.3530	45	SG	V5010
1.495	5.108	.3710	45	SG	V1482
1.495	3.583	.3130	45	3G	V5358
1.495	4.771	.3164	45	SG	V5246
1.495	4.086	.2750	45	SG	V5154
1.496	3.978	.2758	45	SG	V5182
1.496	4.567	.3150	45	SG	V5214
1.496	4.074	.3137	45	SG	V5127
1.496	4.173	.3126	45	SG	V5146
1.496 (38.00MM)	4.251	.3129 (7.95MM)	45	SG	V5091
1.496 (38.00MM)	4.159 (105.64MM)	.3135 (7.96MM)	45	SG	V5076
1.50	4.930	.315	N/A	3G	V1917
1.500	4.920	.3411	45	SG	V1807
1.500	5.028	.3424	44	SG	V1494
1.500	4.355	.3122	45	SG	V1550
1.500	4.713	.3400	45	SG	V1593
1.500	4.923	.3710	45	SG	V1646
1.500	4.541	.3129	45	SG	V1591
1.500	4.940	.3110	46	SG	V1556
1.500	3.314	.2150	45	SG	V5169
1.500	5.014	.3130	45	SG	V5267
1.500	4.935	.3125	45	SG	V5269
1.500	5.156	.3710	45	SG	V0168
1.500	5.093	.3410	45	2G	V0192
1.500	5.736	.3715	45	2G	V0658
1.500	5.569	N/A	45	2G	V0576
1.500	5.281	.3410	44	SG	V0504
1.500	4.900	.3417/.3410	45	2G	V0400
1.500	5.366	.3730	45	SG	V0686
1.500	4.785	.3715	45	2G	V0724
1.500	5.003	.3715	43	2G	V1308
1.500	5.675	.4335	45	2G	V1017
1.500	5.029	.3725	45	SG	V1081
1.500	4.923	.3717	46	2G	V1294
1.500	4.920	.3400	45	2G	V1192
1.500	5.003	.3720/.371	43	4G	V1329
1.500	4.920	.3422	45	2G	V1359
1.500	5.078	.3425/.3418	45	SG	V1361
1.500	4.620	.3422	45	2G	V1437
1.500	4.986	.3417	44	SG	V1433
1.500	4.718	.3412/.3405	45	2G	V1389
1.500	4.807	.3414	45	2G	V1397
1.500	4.982	.3720/.371	45	4G	V1399
1.500	4.792	.3415	45	4G	V5416
1.502	4.688	.3427/.3420	30	SG	V1354

VALVE PROGRESSIVE SIZE CHART (Cont.)

Indexed by Head Diameter

Head Diameter	Overall Length	Stem Diameter	Face Angle	Stem Type	Melling Part No.
1.504 (38.20MM)	4.277 (108.64MM)	.3096/.3106	45	3G	V1244
1.505	5.372	.4343	45	SG	V0917
1.505	4.688	.3425	30	SG	V1549
1.508	5.373	.3704	44	SG	V1217
1.508	5.382	.3704	44	SG	V1332
1.510	5.093	.3410	45	SG	V0375
1.512	5.032	.3725	45	2G	V0794
1.513	5.826	.3410	44	TG	V0608
1.515	5.006	.3410	45	TG	V0348
1.516	5.156	.3410	30	D	V0810
1.516	5.156	.3410	30	SG	V0945
1.516	5.053	.3715	30	2G	V1075
1.516	5.154	.3410	30	SG	V1148
1.516	4.388	.3150	45	SG	V5345
1.518	4.994	.3718/.3711	45	2G	V1419
1.518	5.000	.3715	44	2G	V1312
1.518					V1919
1.520	5.182	.3415	30	SG	V0211
1.522	4.667	.3432/.4667	44	SG	V1323
1.534	4.502	.3110	45	SG	V0874
1.534 (38.96MM)	4.825 (122.56MM)	.3418 (8.68MM)	45	SG	V1464
1.535	5.482	.3720	45	SG	V1431
1.535	5.205	.3150	45	SG	V5101
1.535	5.384	.3163	45	3G	V1546
1.535	4.823	.3417	46	SG	V1559
1.535	5.112	.3710/.3718	45	SG	V1780
1.535	4.524	.273	45	3G	V1914
1.535 (38.99MM)	3.878 (98.50MM)	.3141 (7.98MM)	44	SG	V1343
1.539	5.838	.4340	44	2G	V0183
1.540	4.540	.3715	45	2G	V0981
1.543	5.075	.3418/.3411	44	SG	V1237
1.550	5.016	.3727	45	SG	V1340
1.550	4.920	.320	N/A	SG	V1935
1.558	5.356	.3715	45	SG	V1242
1.559	4.818	.3420	44	SG	V1177
1.559	4.818	.3420	45	SG	V0965
1.560	4.750	.3420	45	SG	V1504
1.562	4.728	.3424	44	SG	V0970
1.562	6.333	.308	45	SG	V0335
1.562	4.954	.3708	44	SG	V1383
1.563	5.908	.3403	45	SG	V0578
1.563	4.540	.3715	45	2G	V0739
1.565	5.911	.3405	45	SG	V0580
1.567	5.884	.3405	45	SG	V1119
1.573	3.577	.3135	45	3G	V5350
1.573	3.883	.3134	45	3G	V5351
1.573 (39.95MM)	4.164 (105.76MM)	.3165 (8.04MM)	44	SG	V1285
1.575	5.156	.3720	44	2G	V1233
1.575	4.819	.3137	45	3G	V5348
1.575	4.319	.3149	45	SG	V5316
1.575	4.567	.3150	45	SG	V5216
1.575	4.495	.3145	45	SG	V5049
1.575	4.606	.3150	45	SG	V5275
1.575	5.469	.2737	44.30	SG	V5522
1.576	4.258	.3140	45	SG	V5322
1.578	4.814	.3130	45	SG	V5274
1.584	6.444	.3421	30	SG	V0327
1.588	6.440	.3420	30	SG	V0411

VALVE PROGRESSIVE SIZE CHART (Cont.)

Indexed by Head Diameter

Head Diameter	Overall Length	Stem Diameter	Face Angle	Stem Type	Melling Part No.
1.588 (40.34MM)	4.358 (110.69MM)	.3130 (7.95MM)	45	SG	V5094
1.594	6.700	.4340	45	2G	V0159
1.595	5.676	.3720	37	SG	V1542
1.598	4.418	.3127	45	SG	V1541
1.598	4.498	.3127	45	SG	V1555
1.598	4.498	.3130	45	SG	V1553
1.598 (40.59MM)	4.418 (112.22MM)	.3128 (7.95MM)	45	SG	V1449
1.600	5.787	.3722	45	SG	V1422
1.600	4.995	.3710	45	4G	V1401
1.600	4.880	.3417/.3410	45	SG	V1372
1.600	4.700	.3135	45	SG	V1466
1.600	4.903	.3415	45	2G	V0919
1.600	5.001	.3715/.3705	47	4G	V1307
1.600	5.000	.3715	43	2G	V1309
1.600	4.989	.3715	45	2G	V1675
1.600	5.119	.3422	45	2G	V1440
1.600 (40.64MM)	4.700 (119.38MM)	.3418/.3410	45	2G	V1395
1.604	6.352	.3415	45	2G	V0691
1.609	5.473	.3720	45	SG	V0559
1.610	4.782	.3420	44	4G	V1528
1.613	4.193	.3138	44	SG	V1486
1.614	4.208	.3140	45	SG	V5160
1.616	4.292	.3135	45	SG	V5017
1.616	5.468	.3715	45	TG	V0412
1.616	4.995	.3712	45	2G	V1417
1.618	4.161	.2755	45	SG	V5264
1.620	3.994	.3414	45	SG	V1338
1.620	4.769	.3725	45	2G	V0567
1.620	4.216	.2745	45	SG	V5270
1.622	4.787	.342	45	SG	V1324
1.622	4.708	.3424	30	SG	V1212
1.624	4.695	.3427/.3420	44	SG	V0974
1.624	4.919	.3108/.3115	44	SG	V1715
1.625	5.246	.3415	44	SG	V1083
1.625	5.160	.3727	45	SG	V1104
1.625	4.907	.3725/.3715	44	SG	V1047
1.625	4.675	.3412/.3402	45	SG	V1353
1.625	4.600	.3414	45	SG	V1182
1.635	5.702	.4339	44	SG	V0530
1.641	5.532	.3406	30	2G	V0867
1.644	5.931	.3418	44	SG	V0609
1.647	5.087	.3420	44	SG	V0376
1.649	4.261	.3104	44	SG	V1268
1.653	4.983	.3423/.3416	45	SG	V1271
1.653	5.085	.3423/.3416	44	SG	V1102
1.653	5.103	.3715	45	SG	V1483
1.653	5.003	.3419	45	SG	V1547
1.653 (41.99MM)	4.376 (111.15MM)	.3167/.3160	46	3G	V1200
1.6535	4.980	.3417/.3413	45	SG	V1832
1.654	5.303	.3163	44	3G	V1452
1.654 (42.01MM)	4.276 (108.61MM)	.3163 (8.03MM)	45	SG	V5061
1.655	4.129	.3163	45	SG	V5385
1.655	5.052	.3418/.3411	44	4G	V1269
1.655	5.053	.3418/.3411	46	SG	V1367
1.655	5.053	.3448/.3443	46	SG	V1367+3
1.656	5.844	.3715	45	SG	V0203
1.658 (42.11MM)	4.576 (116.23MM)	.3141 (7.98MM)	45	SG	V5015
1.660	5.367	.3713	46	SG	V0996

VALVE PROGRESSIVE SIZE CHART (Cont.)

Indexed by Head Diameter

Head Diameter	Overall Length	Stem Diameter	Face Angle	Stem Type	Melling Part No.
1.660	5.367	.3711	46	SG	V1235
1.660	4.948	.3411	44	2G	V1245
1.660	5.250	.336	45	SG	V1153
1.660	4.979	.3140	45	SG	V5266
1.661	4.615	.3130	45	3G	V1536
1.668 (42.37MM)	4.313 (109.55MM)	.3130 (7.95MM)	45	SG	V5087
1.672	4.954	.3708	44	SG	V1385
1.679	6.038	.3720	45	SG	V0922
1.680	4.910	.3725/.3715	44	SG	V1179
1.680	5.799	.312	N/A	SG	V1785
1.680	5.799	.3122	N/A	SG	V1786
1.682	4.914	.3720	44	SG	V1257
1.682	5.164	.3419	44	SG	V1416
1.688	5.163	.3710	45	2G	V0169
1.688	5.700	.3720	44	2G	V0659
1.690	4.051	.3135	45	SG	V5147
1.690	4.088	.2758	45	SG	V5117
1.691(42.95MM)	4.230 (107.44MM)	.3130	45	SG	V5088
1.693	4.323	.3137	45	SG	V5141
1.693	5.456	.3136	45	SG	V1569
1.693 (43.00MM)	4.450 (113.03MM)	.3135 (7.96MM)	45	SG	V5065
1.696 (43.08MM)	4.553 (115.65MM)	.3139 (7.97MM)	44	SG	V5048
1.710	4.730	.3407	45	SG	V1711
1.710	4.713	.3412/.3402	45	SG	V1388
1.710	5.058	.3418/.3411	44	SG	V1173
1.714	6.232	.3722	45	2G	V1288
1.715	6.191	.3720	30	2G	V1403
1.715	6.133	.3723	44	SG	V1375
1.718	6.670	.4340	45	2G	V0160
1.718	4.705	.3140	45	SG	V1561
1.718 (43.64MM)	4.706 (119.53MM)	.3413 (8.67MM)	45	2G	V1481
1.720	5.355	.3717	45	SG	V1261
1.720	5.077	.3425/.3418	45	GS	V1362
1.720	4.924	.3420	45	SG	V1360
1.720	4.669	.3425/.3418	45	2G	V1438
1.720	4.912	.3413	45	2G	V0399
1.720	4.912	.3449	45	2G	V0399+3
1.720	5.293	.3717	45	SG	V1578
1.720	4.588	.3135	45	SG	V1592
1.720	4.394	.3135	45	SG	V1551
1.720	5.392	.3717	45	SG	V2126
1.725	5.068	.3420	45	SG	V1165
1.725	4.978	.3420	45	SG	V1229
1.727	5.981	.3723	45	2G	V1648
1.732	5.457	.3136	45	SG	V1705
1.732	5.465	.2745	45	SG	V1736
1.732	5.268	.316	45	3G	V2044
1.732	5.265	.2746	45	SG	V1902
1.733	4.230	.3136	45	SG	V5335
1.734	5.473	.4145	45	SG	V1133
1.735	4.787	.3419	45	4G	V5415
1.736	4.498	.3139	45	SG	V5279
1.736	7.250	.403	45	SG	V0678
1.736	4.280	.3120	45	SG	V5222
1.737 (44.12MM)	4.790 (121.67MM)	.3423/.3416	44	4G	V1398
1.739 (44.17MM)	4.767 (121.72MM)	.3423/.3416	44	4G	V1304
1.740	4.897	.3715	45	2G	V1281
1.740	4.884	.3725/.3718	45	4G	V1156

VALVE PROGRESSIVE SIZE CHART (Cont.)

Indexed by Head Diameter

Head Diameter	Overall Length	Stem Diameter	Face Angle	Stem Type	Melling Part No.
1.750	4.986	.3417	44	SG	V1434
1.750	4.621	.2750	45	3G	V1699
1.750	5.018	.3420	44	SG	V1495
1.750 (44.45MM)	4.667 (118.54MM)	.3428 (8.71MM)	45	SG	V1450
1.752	5.400	.3715	44	SG	V1348
1.752	5.392	.3715	44	SG	V1349
1.752	5.392	.3714	44	SG	V0918
1.752	5.392	.3712	45	SG	V0949
1.752	5.392	.3715	44	SG	V1057
1.753	4.261	.3104	45	SG	V1357
1.770	5.082	.3414/.3407	44	2G	V1097
1.770	7.140	.3717	30	2G	V1462
1.770	4.806	.3470	45	SG	V1594
1.770	4.465	.3135	45	SG	V5328
1.770	5.052	.3414/.3407	44	2G	V1158
1.777	5.750	.4340	44	TG	V0397
1.779	4.818	.3420	45	SG	V0963
1.779	4.818	.3420	44	SG	V1120
1.780	4.863	.3420	45	SG	V0947
1.780	4.865	.3423/.3416	44	SG	V1001
1.781	5.055	.3423/.3416	44	SG	V1137
1.781	5.055	.3453/.3446	44	SG	V1137+3
1.782	5.070	.3424/.3414	44	SG	V1328
1.782	4.838	.3420	45	4G	V1470
1.782	4.941	.3424/.3414	45	SG	V1538
1.782	4.840	.2750	45	SG	V1790
1.783	4.749	.3420	45	SG	V1505
1.783	4.426	.3150	45	SG	V5344
1.783	5.146	.3715	44	SG	V1384
1.783	5.152	.3713	44	SG	V1382
1.787	4.906	.3720	29	SG	V1442
1.787	4.899	.3720	29	4G	V1260
1.787	4.899	.3720	29	SG	V1046
1.787	4.869	.3722	29	4G	V0550
1.791	4.949	.3127	45	2G	V1671
1.804	5.683	.3050	45	2G	V1378
1.805	6.343	.4335	44	3G	V1301
1.805	6.343	.4335	44	SG	V1074
1.810	4.917	.3142	45	3G	V5070
1.811	4.524	.274	45	3G	V1913
1.811	5.110	.3413	45	SG	V1484
1.811	4.198	.3100	45	SG	V5143
1.811	4.252	.3134	45	SG	V5145
1.811	5.000	.373	45	2G	V1186
1.811 (46.00MM)	4.331 (110.00MM)	.3137 (7.97MM)	45	SG	V5092
1.825	5.900	.4343	45	SG	V0707
1.840	5.255	.3715	45	SG	V0997
1.840	5.355	.3720/.3713	45	SG	V1080
1.840	4.912	.3414	45	2G	V1393
1.844	5.070	.3423/.3416	44	SG	V1238
1.860	4.850	.275	45.625	3G	V1789
1.875	4.667	.3432/.3425	44	SG	V1263
1.875	5.018	.3429	44	SG	V1370
1.875	5.009	.3725	45	SG	V1082
1.875	4.740	.3429	44	SG	V0969
1.875	7.066	.4505	30	2G	V0602
1.875	6.386	.3414	30	2G	V0308
1.877	5.688	.3720	30	SG	V1543

VALVE PROGRESSIVE SIZE CHART (Cont.)

Indexed by Head Diameter

Head Diameter	Overall Length	Stem Diameter	Face Angle	Stem Type	Melling Part No.
1.880	5.668	.3725	45	4G	V0577
1.880	4.981	.3715/.3725	45	2G	V1180
1.882	5.900	.4341	45	SG	V1026
1.890	4.969	.2734	45	4G	V1993
1.890	4.880	.318	N/A	SG	V1934
1.896	5.469	.3717	30	2G	V1205
1.898	6.248	.3720	45	2G	V1289
1.902	6.151	.3720	44	2G	V1336
1.910	4.911	.3115	45	SG	V1479
1.910	4.880	.314	N/A	3G	V1916
1.910	4.912	.3115	46	SG	V1557
1.913	5.900	.4347	30	SG	V1254
1.915	4.481	.2734	45	3G	V1918
1.920	4.905	.3115	44	SG	V1714
1.924	5.961	.3728	45	SG	V1649
1.925	5.110	.3420	45	SG	V0494
1.940	4.880	.3422/.3415	45	SG	V0696
1.940	4.880	.3572/.3565	45	SG	V0696+15
1.940	4.880	.3452/.3445	45	SG	V0696+3
1.940	4.880	.3414	45	2G	V1195
1.940	4.880	.3411	45	1G	V1931
1.940	4.880	.3564	45	2G	V1195+15
1.940	4.880	.3434	45	2G	V1195+3
1.969	5.223	.3725	45	2G	V0560
1.982	5.195	.3415	45	SG	V1548
1.995	4.667	.3432/.3425	44	SG	V1457
2.000	5.140	.3725	45	SG	V1105
2.020	4.880	.3412/.3407	45	2G	V0988
2.020	5.742	.4354	45	SG	V0531
2.025	4.899	.3725/.3715	29	SG	V1048
2.025	4.899	.3720	30	4G	V1258
2.032	5.450	.3720/.3710	44	SG	V0637
2.040	5.238	.3423/.3416	44	SG	V1380
2.041	5.230	.3423/.3416	44	4G	V1270
2.054	5.467	.3725	44	SG	V1432
2.065	5.149	.3709	45	SG	V1386
2.065	5.225	.3722/.3715	45	SG	V1107
2.074	6.099	.4345	14	SG	V1507
2.078	5.249	.3725	30	SG	V1152
2.080	4.868	.3720	45	SG	V1157
2.080	4.879	.3721	45	2G	V1282
2.080	4.864	.3727	45	2G	V0548
2.083	5.204	.3423/.3416	45	SG	V1272
2.083	5.175	.3419	45	SG	V1723
2.110	4.979	.3419/.3412	29	2G	V1161
2.110	5.093	.3419/.3412	29	2G	V1098
2.110	5.062	.3419/.3412	29	2G	V1077
2.157	6.341	.4345	14	SG	V0512
2.157	6.341	.4345	14	SG	V1355
2.187	5.231	.3719	45	SG	V2101
2.190	5.214	.3722/.3715	45	SG	V1164
2.192	5.234	.3423/.3416	44	SG	V1174
2.200	5.185	.3420	30	SG	V1230
2.245	5.288	.3423/.3416	29	SG	V1166
2.250	5.866	.4345	15	2G	V1221
2.300	5.192	.3722/.3715	45	G	V1136