

NEW!



GM LS Gen III Gen IV Engines

Hydraulic Roller 3 Bolt Performance Camshafts



Part No.	Class	Dur. @ .050	Valve Lift	Lobe Separation	RPM Range	Additional Description	
22307	Class III	218/227	523/524	112	Idle - 5000	Non-AFM	Non-VVT
22411	Class IV	225/236	525/525	110	2000-6000	Non-AFM	Non-VVT
22413	Class IV	229/240	551/551	108	2000-6000	Non-AFM	Non-VVT
22412	Class IV	236/246	612/612	110	2000-6500	Non-AFM	Non-VVT
22500	Class V	234/277	595/595	107	2000-6000	Non-AFM	Non-VVT

GM 4.8L 1999-17 • GM 5.3L 1999-16 • GM 5.7L 1997-05 • GM 6.0L 1999-16 • GM 6.2L 2007-17

High Performance LS Valve Springs



Part No.	Spring Type	OD Top/Bottom	ID Top/Bottom	Closed Height/Pressure	Open Height/Pressure	Solid Height
46652	Beehive	1.029"/1.264"	.665"/.890"	1.800"/130	1.200"/325	1.146" Max
46656	Dual	1.276"	.668"	1.800"/147	1.230"/406	1.100" Max
VS-2257	Beehive	1.044"/1.250"	.638"/.838"	1.800"/95	1.200"/300	1.143" Max

****Always consult the Melling catalog for correct fitment****

