

**NOW
AVAILABLE!**



ANNOUNCES

A NEW VALVE SPRING FOR HEAVY DUTY & INDUSTRIAL APPLICATIONS

ADVANCE MIXER	24V	10.3L, 12.0L
AMERICAN LaFRANCE	24V	10.3L, 11.1L, 12.0L, 12.5L
AUTOCAR	24V	10.3L, 11.1L
BLUE BIRD	24V	12.0L, 12.5L
BERING	24V	12.0L
CATERPILLAR	24V	10.3L, 11.1L, 12.0L, 12.5L
COUNTRY COACH	24V	10.3L, 12.0L, 12.5L
CRANE CARRIER	24V	10.3L, 11.1L, 12.0L, 12.5L
FORD	24V	10.3L, 12.0L
FREIGHTLINER	24V	10.3L, 11.1L, 12.0L, 12.5L
GILLIG	24V	10.3L, 12.0L
INDIANA PHOENIX	24V	10.3L, 12.0L, 12.5L
INTERNATIONAL	24V	10.3L, 11.1L, 12.0L, 12.5L

KENWORTH	24V	10.3L, 11.1L, 12.0L, 12.5L
MOTOR COACH IND.	24V	10.3L, 12.0L, 12.5L
OSHKOSH MOTOR TRUCK	24V	10.3L, 11.1L, 12.0L, 12.5L
PETERBUILT	24V	10.3L, 11.1L, 12.0L, 12.5L
PIERCE	24V	10.3L, 12.0L, 12.5L
ROADMASTER RAIL	24V	11.1L, 12.0L, 12.5L
SPARTAN MOTORS	24V	10.3L, 12.0L, 12.5L
STERLING TRUCK	24V	10.3L, 11.1L, 12.0L, 12.5L
TEREX	24V	12.0L
VAN HOOL	24V	12.5L
VOLVO	24V	10.3L
WESTERN STAR	24V	10.3L, 11.1L, 12.0L, 12.5L
WHITE GMC	24V	10.3L

Dual Spring (Outer Spring)
Qty Required 24

Part number

VS-1463

UPC: 729295205524



Replaces OE# 214-0586, 332-2152 & 7W7082

Closed Height/Load	Open Height/Load	Solid Height	O.D.	I.D.	Free Length	Coils
2.000"/50.80mm @ 90	1.425"/36.88mm @ 203	1.227"/32.43mm	1.336"/33.93mm	.972"/24.69mm	2.484"/63.09mm	7.50 RH

**** Always consult catalog listings for detailed application information****

Melling Engine Parts

P.O. Box 1188 • Jackson, MI 49204 • www.melling.com