



NEW CHRYSLER HEMI HIGH PERFORMANCE CAMSHAFTS

CLASS 1 AND CLASS 2 HIGH PERFORMANCE CAMSHAFTS
FOR CHRYSLER 5.7L, 6.1L, 6.2L & 6.4L HEMI ENGINES



Part # 23107

CLASS 1 HYDRAULIC

ROLLER CAMSHAFT

- RPM Range: 1000-5000
- For Non MDS Engines Without VVT
- Single Bolt
- 114° Lobe Separation
- 0.520" Intake Valve Lift
- 0.520" Exhaust Valve Lift
- Intake Duration @ .050 Inch Lift 211°
- Exhaust Duration @ .050 Inch Lift 215°

Part # 23207

CLASS 2 HYDRAULIC

ROLLER CAMSHAFT

- RPM Range: 1200-5000
- For Non MDS Engines Without VVT
- Single Bolt
- 114° Lobe Separation
- 0.575" Intake Valve Lift
- 0.575" Exhaust Valve Lift
- Intake Duration @ .050 Inch Lift 213°
- Exhaust Duration @ .050 Inch Lift 219°

Part # 23108

CLASS 1 HYDRAULIC

ROLLER CAMSHAFT

- RPM Range: 1000-5000
- For Non MDS Engines With VVT
- Single Bolt
- 114° Lobe Separation
- 0.520" Intake Valve Lift
- 0.520" Exhaust Valve Lift
- Intake Duration @ .050 Inch Lift 211°
- Exhaust Duration @ .050 Inch Lift 215°

Part # 23208

CLASS 2 HYDRAULIC

ROLLER CAMSHAFT

- RPM Range: 1200-5200
- For Non MDS Engines With VVT
- Single Bolt
- 114° Lobe Separation
- 0.575" Intake Valve Lift
- 0.575" Exhaust Valve Lift
- Intake Duration @ .050 Inch Lift 213°
- Exhaust Duration @ .050 Inch Lift 219°



MELLING.COM/CATEGORY/PERFORMANCE