

MELLING™

PERFORMANCE

NEW HIGH PERFORMANCE GM LS CAMSHAFTS FOR GEN 3 AND GEN 4 ENGINES



PART# 22307

CLASS 3 HYDRAULIC ROLLER PERFORMANCE CAMSHAFT

- RPM Range: Idle - 5000
- For Non AFM Engines
- 3 Bolt Non VVT
- 112° Lobe Separation
- 0.523" Intake Valve Lift
- 0.524" Exhaust Valve Lift
- Intake Duration @ .050 Inch Lift 218°
- Exhaust Duration @ .050 Inch Lift 227°

PART# 22411

CLASS 4 HYDRAULIC ROLLER PERFORMANCE CAMSHAFT

- RPM Range: 2000 - 6000
- For Non AFM Engines
- 3 Bolt Non VVT
- 110° Lobe Separation
- 0.525" Intake Valve Lift
- 0.525" Exhaust Valve Lift
- Intake Duration @ .050 Inch Lift 225°
- Exhaust Duration @ .050 Inch Lift 236°

PART# 22412

CLASS 4 HYDRAULIC ROLLER PERFORMANCE CAMSHAFT

- RPM Range: 2000 - 6500
- For Non AFM Engines
- 3 Bolt Non VVT
- 110° Lobe Separation
- 0.612" Intake Valve Lift
- 0.612" Exhaust Valve Lift
- Intake Duration @ .050 Inch Lift 236°
- Exhaust Duration @ .050 Inch Lift 245°

PART# 22413

CLASS 4 HYDRAULIC ROLLER PERFORMANCE CAMSHAFT

- RPM Range: 2000 - 6000
- For Non AFM Engines
- 3 Bolt Non VVT
- 108° Lobe Separation
- 0.551" Intake Valve Lift
- 0.551" Exhaust Valve Lift
- Intake Duration @ .050 Inch Lift 229°
- Exhaust Duration @ .050 Inch Lift 240°

PART# 22500

CLASS 5 HYDRAULIC ROLLER PERFORMANCE CAMSHAFT

- RPM Range: 2000 - 6000
- For Non AFM Engines
- 3 Bolt Non VVT
- 107° Lobe Separation
- 0.595" Intake Valve Lift
- 0.595" Exhaust Valve Lift
- Intake Duration @ .050 Inch Lift 234°
- Exhaust Duration @ .050 Inch Lift 277°

PART# 22206

CLASS 2 HYDRAULIC ROLLER PERFORMANCE CAMSHAFT

- RPM Range: Idle - 5000
- For Non AFM Engines
- 3 Bolt Non VVT
- 111° Lobe Separation
- 0.553" Intake Valve Lift
- 0.553" Exhaust Valve Lift
- Intake Duration @ .050 Inch Lift 212°
- Exhaust Duration @ .050 Inch Lift 218°



FLIP OVER FOR MORE

NEW HIGH PERFORMANCE GM LS CAMSHAFTS FOR GEN 3 AND GEN 4 ENGINES

PART# 22207

CLASS 2 HYDRAULIC ROLLER PERFORMANCE CAMSHAFT

- RPM Range: Idle - 5000
- For Non AFM Engines
- 3 Bolt Non VVT
- 112° Lobe Separation
- 0.604" Intake Valve Lift
- 0.604" Exhaust Valve Lift
- Intake Duration @ .050 Inch Lift 212°
- Exhaust Duration @ .050 Inch Lift 218°

PART# 22323

CLASS 3 HYDRAULIC ROLLER PERFORMANCE CAMSHAFT

- RPM Range: 1800 - 5400
- For Non AFM Engines
- 3 Bolt Non VVT
- 110° Lobe Separation
- 0.553" Intake Valve Lift
- 0.553" Exhaust Valve Lift
- Intake Duration @ .050 Inch Lift 218°
- Exhaust Duration @ .050 Inch Lift 224°

PART# 22324

CLASS 3 HYDRAULIC ROLLER PERFORMANCE CAMSHAFT

- RPM Range: 1800 - 5400
- For Non AFM Engines
- 3 Bolt Non VVT
- 109° Lobe Separation
- 0.553" Intake Valve Lift
- 0.553" Exhaust Valve Lift
- Intake Duration @ .050 Inch Lift 224°
- Exhaust Duration @ .050 Inch Lift 230°

PART# 22325

CLASS 3 HYDRAULIC ROLLER PERFORMANCE CAMSHAFT

- RPM Range: 1800 - 5400
- For Non AFM Engines
- 3 Bolt Non VVT
- 112° Lobe Separation
- 0.604" Intake Valve Lift
- 0.604" Exhaust Valve Lift
- Intake Duration @ .050 Inch Lift 218°
- Exhaust Duration @ .050 Inch Lift 224°

PART# 22326

CLASS 3 HYDRAULIC ROLLER PERFORMANCE CAMSHAFT

- RPM Range: 1800 - 5400
- For Non AFM Engines
- 3 Bolt Non VVT
- 112° Lobe Separation
- 0.604" Intake Valve Lift
- 0.604" Exhaust Valve Lift
- Intake Duration @ .050 Inch Lift 224°
- Exhaust Duration @ .050 Inch Lift 230°

PART# 22327

CLASS 3 HYDRAULIC ROLLER PERFORMANCE CAMSHAFT

- RPM Range: 1800 - 5400
- For Non AFM Engines
- 3 Bolt Non VVT
- 112° Lobe Separation
- 0.625" Intake Valve Lift
- 0.625" Exhaust Valve Lift
- Intake Duration @ .050 Inch Lift 224°
- Exhaust Duration @ .050 Inch Lift 230°

PART# 22328

CLASS 3 HYDRAULIC ROLLER PERFORMANCE CAMSHAFT

- RPM Range: 1800 - 5400
- For Non AFM Engines
- 3 Bolt Non VVT
- 112° Lobe Separation
- 0.625" Intake Valve Lift
- 0.625" Exhaust Valve Lift
- Intake Duration @ .050 Inch Lift 226°
- Exhaust Duration @ .050 Inch Lift 238°

PART# 22422

CLASS 4 HYDRAULIC ROLLER PERFORMANCE CAMSHAFT

- RPM Range: 2000 - 6000
- For Non AFM Engines
- 3 Bolt Non VVT
- 112° Lobe Separation
- 0.625" Intake Valve Lift
- 0.625" Exhaust Valve Lift
- Intake Duration @ .050 Inch Lift 228°
- Exhaust Duration @ .050 Inch Lift 234°

PART# 22423

CLASS 4 HYDRAULIC ROLLER PERFORMANCE CAMSHAFT

- RPM Range: 2000 - 6000
- For Non AFM Engines
- 3 Bolt Non VVT
- 112° Lobe Separation
- 0.625" Intake Valve Lift
- 0.625" Exhaust Valve Lift
- Intake Duration @ .050 Inch Lift 232°
- Exhaust Duration @ .050 Inch Lift 240°

PART# 22424

CLASS 4 HYDRAULIC ROLLER PERFORMANCE CAMSHAFT

- RPM Range: 2000 - 6000
- For Non AFM Engines
- 3 Bolt Non VVT
- 112° Lobe Separation
- 0.625" Intake Valve Lift
- 0.625" Exhaust Valve Lift
- Intake Duration @ .050 Inch Lift 236°
- Exhaust Duration @ .050 Inch Lift 244°

PART# 22425

CLASS 4 HYDRAULIC ROLLER PERFORMANCE CAMSHAFT

- RPM Range: 2000 - 6000
- For Non AFM Engines
- 3 Bolt Non VVT
- 113° Lobe Separation
- 0.625" Intake Valve Lift
- 0.625" Exhaust Valve Lift
- Intake Duration @ .050 Inch Lift 230°
- Exhaust Duration @ .050 Inch Lift 244°

PART# 22501

CLASS 5 HYDRAULIC ROLLER PERFORMANCE CAMSHAFT

- RPM Range: 2500 - 6500
- For Non AFM Engines
- 3 Bolt Non VVT
- 113° Lobe Separation
- 0.625" Intake Valve Lift
- 0.625" Exhaust Valve Lift
- Intake Duration @ .050 Inch Lift 234°
- Exhaust Duration @ .050 Inch Lift 248°

PART# 22502

CLASS 5 HYDRAULIC ROLLER PERFORMANCE CAMSHAFT

- RPM Range: 2500 - 6500
- For Non AFM Engines
- 3 Bolt Non VVT
- 113° Lobe Separation
- 0.625" Intake Valve Lift
- 0.625" Exhaust Valve Lift
- Intake Duration @ .050 Inch Lift 238°
- Exhaust Duration @ .050 Inch Lift 252°



MELLING
PERFORMANCE

Visit melling.com/category/performance
to view all of our product announcements!